

Commander® Series

Area Lighting



FEATURES

- Generates up to 28K lumens of super bright white light
- Available in 12/24 Vdc or 120 Vac
- Regardless of power source — same high-powered light output
- Slimmest LED lamp head profile in the industry
- Instant-on at full intensity
- Innovative cooling fins provide higher efficiency and more light
- Advanced lens and arrangement of LEDs generate a uniform flood and spot combination light pattern
- White bezels included (except for surface mount lights)
- Surface mount lights only available with Chrome bezel
- Five-year warranty

APPROVALS

- IP68
- AC models are UL approved

Full Function Area Light

Commander® Series provides the widest light pattern for improved work area visibility as well as illuminating objects at a farther distance. Advanced lens and a unique arrangement of LEDs generate a uniform flood and spot combination of light patterns. This scene light has three rows of LEDs. The top and bottom rows are flood LEDs designed to light up the work area. The middle row of focused spot LEDs provides long distance illumination. Unique lens design illuminates area directly below lamp head.

Surface Mount

Commander Series is available in a low-profile LED surface mount to contour the shape of your emergency vehicle. These models come standard with a Chrome bezel. The surface mount models are available in 12/24 Vdc and 120 Vac.

Portable Commander Series

The portable Commander Series models can be moved to a specific location with the use of the rubber molded handle. This handle stays cool when the lamp head is illuminated. Portable models are available in 120 Vac with a NEMA L5-15 3-prong Twist Lock plug.



Commander provides both work area and distance illumination.

HOW TO ORDER

LED Color Lens Color
W C

12/24 VDC MODELS

COM15K	Commander, 15K lumens, 12/24 Vdc, spot/flood LED light head
COM15K-260	Commander, 15K lumens, 12/24 Vdc, low-profile surface mount light head
COM15K-530	Commander, 15K lumens, 12/24 Vdc, side mount push-up pole, 2.75-inch offset brackets
COM15K-530SW	Commander, 15K lumens, 12/24 Vdc, side mount push-up pole, 2.75-inch offset brackets, raised pole indicator
COM15K-570	Commander, 15K lumens, 12/24 Vdc, fixed top mount
COM20K	Commander, 20K lumens, 12/24 Vdc, spot/flood LED light head
COM20K-530SW	Commander, 20K lumens, 12/24 Vdc, side mount push-up pole, 2.75-inch offset brackets, raised pole indicator
COM20K-ON-530SW	Commander, 20K lumens, 12/24 Vdc, on/off switch, side mount push-up pole, 2.75-inch offset brackets, raised pole indicator
COMX-DC-260	Commander Plus, 28K lumens, 12/24 Vdc, low-profile surface mount light head
COMX-DC-530	Commander Plus, 28K lumens, 12/24 Vdc, side mount push-up pole, 2.75-inch offset brackets
COMX-DC-530SW	Commander Plus, 28K lumens, 12/24 Vdc, side mount push-up pole, 2.75-inch offset brackets, raised pole indicator
COMX-S-DC-570	Commander Plus-S, 28K lumens, 12/24 Vdc, fixed top mount

120 VAC MODELS

COM120	Commander, 20K lumens, 120 Vac, spot/flood LED light head
COM120-260	Commander, 20K lumens, 120 Vac, low-profile surface mount light head
COM120-570	Commander, 20K lumens, 120 Vac, fixed top mount
COM120-ON	Commander, 20K lumens, 120 Vac, on/off switch

COM120-ON-530	Commander, 20K lumens, 120 Vac, on/off switch, side mount push-up pole, 2.75-inch offset brackets
COM120-ON-530SW	Commander, 20K lumens, 120 Vac, on/off switch, side mount push-up pole, 2.75-inch offset brackets, raised pole indicator
COM120-ON-600-603	Commander, 20K lumens, 120 Vac, on/off switch, large tripod and quick-release bracket, L5-15 3-prong twist lock plug
COMX-120-ON-530	Commander Plus, 28K lumens, 120 Vac, on/off switch, side mount push-up
COMX-120-ON-600-603-P3	Commander Plus, 28K lumens, 120 Vac, on/off switch, large tripod and quick-release bracket, L5-15 3-prong twist lock plug

SPECIFICATIONS

LIGHT HEAD PHYSICAL DIMENSIONS

LENGTH	14.0 in (35.6 cm)
WIDTH	3.8 in (9.5 cm)
HEIGHT	11.0 in (27.9 cm)

TRIPOD DIMENSIONS

TOTAL HEIGHT WITH LIGHT HEADS (Pole & Legs Retracted)	72.0 in (182.9 cm)
---	--------------------

SIDE MOUNT PUSH-UP POLE DIMENSIONS

OVERALL HEIGHT	58.0 in (147.3 cm)
INNER POLE EXTENSION	20.0 in (5.8 cm)

TECHNICAL SPECIFICATIONS

	VOLTS	CURRENT DRAW	LUMENS
COM15K	12/24 Vdc	13.9/6.9 A	15K
COM20K	12/24 Vdc	18.3/9.2 A	20K
COM120	120 Vac	1.8 A	20K
COMX-DC	12/24 Vdc	19.2/9.6 A	28K
COMX-120	120 Vac	2.8 A	28K

