

MicroPulse® 650/652

Exterior Perimeter Light



FEATURES

- Multiple mounting options for various applications
- Superior warning with (6) or (12) high-powered LEDs
- Single- and dual-color models are available
- LEDs offered in Amber, Blue, Red, and White
- Single/multi-unit synchronization
- Five-year warranty

High-Performance LEDs Provide First-Responder and Work Truck Vehicles with Superior Auxiliary Warning Capability

Compact MicroPulse® perimeter lights feature an advanced high-output LED light head for additional warning around the outside of your vehicle.

Multiple Mounting options for Various Applications

Available in single- and dual-color models, MicroPulse lights can be programmed to operate as a single unit or in synchronization with multiple MicroPulse light heads. Built-in flash patterns enable multiple vehicle perimeter lights to be synchronized in the same pattern or reverse sequence.

Built to Last

The MicroPulse lens is made of UV-resistant polycarbonate to protect against harsh conditions. Certified to meet IP67, MicroPulse perimeter lights have a fully encapsulated water-proof housing that provides a barrier against dust, moisture, and water.

APPROVALS

- IP67
- SAE J845, Class 1
- SAE J595, Class 1

MicroPulse Delivers Optimum Flexibility Through a Choice of Different Colors and Color Combinations

LED colors include Red, Blue, White, and Amber as well as dual-color models in Red/Blue, Blue/White, Red/White, and White/Amber combinations.



MPS650-WW
Grille/Hood Mount Model



MPS650/MPS652
Grille/Hood Mount Model



MPS650-BB and MPS650-RR
Mounted on Hood

HOW TO ORDER

MICROPULSE 6, SINGLE-COLOR , HOOD/GRILLE MOUNT


MPS650-AA	(6) Amber LEDs, Clear lens
MPS650-BB	(6) Blue LEDs, Clear lens
MPS650-RR	(6) Red LEDs, Clear lens
MPS650-WW	(6) White LEDs, Clear lens

MICROPULSE 6, DUAL-COLOR, HOOD/GRILLE MOUNT

MPS652-BR	(6) Blue LEDs, (6) Red LEDs, Clear lens
MPS652-BW	(6) Blue LEDs, (6) White LEDs, Clear lens
MPS652-RW	(6) Red LEDs, (6) White LEDs, Clear lens
MPS652-WA	(6) White LEDs, (6) Amber LEDs, Clear lens

ACCESSORIES

MPSM650-SPACRKT	Kit of (4) 5-degree rubber mounting wedges for use with (2) MPS650 lights
-----------------	---



MPSM650-SPACRKT

SPECIFICATIONS

OPERATING VOLTAGE	12/24 Vdc
CURRENT DRAW	0.55 A @ 12 Vdc 0.26 A @ 24 Vdc
OPERATING TEMP.	-40° to +176° F (-40° to +80° C)

PHYSICAL SPECIFICATIONS

LENGTH	4.2 in (10.8 cm)
WIDTH	1.7 in (4.3 cm)
HEIGHT	0.9 in (2.4 cm)

SHIP WEIGHT

0.75 lb (0.34 kg)

